CLAIMS

What is claimed is:

1. A method for transmitting a loopback cell within a switching node of an ATM connection, said switching node including a first adapter having associated ports and a second adapter having associated ports, wherein said loopback cell enters said switching node by a first adapter port, said method comprising:

detecting a loopback condition when an ATM cell enters said first adapter; and

in response to a loopback condition:

appending a routing label to said ATM cell indicating that said ATM cell is a loopback cell to be looped back on said ATM connection; and

transferring said loopback cell to said first adapter port utilizing said appended routing label.

2. The method of claim 1, wherein said appending step is preceded by the step of identifying said ATM cell within said first adapter.

3. The method of claim 2, wherein said identifying said ATM cell is performed with respect to said first adapter port and a virtual path/virtual circuit encoded on said ATM cell.

4.   The method of claim 1, wherein said detecting step comprises reading a loop condition bit from a dedicated register.

5.   The method of claim 1, wherein said transferring step further comprises:

switching said ATM cell to said second adapter from said first adapter; and

switching said ATM cell back to said to said first adapter from said second adapter.

6.   The method of claim 1, wherein said routing label is appended to said loopback cell only if a loop control bit is set by a control point of said switching node within said first adapter.

7.   The method of claim 6, further comprising, in response to a loopback condition, setting said loop control bit within said first adapter.

8.   The method of claim 6, further comprising adding a loopback flag to said loopback cell if said loop control bit is set, wherein said loopback flag serves as an indicator for a protocol engine within said first adapter that said routing labels have to be appended to said loopback cell.

1   9.   The method of claim 1, wherein said routing label
2   includes a switch routing label for identifying said
3   first adapter as the output adapter from which said
4   loopback cell will exit said switching node.

1   10.   The method of claim 1, wherein said routing label
2   includes a protocol engine correlator for pointing to a
3   connection control block within said first adapter.

1   11.   The method of claim 1, wherein the ATM header
2   virtual path/virtual circuit of said loopback cell is not
3   swapped by the protocol engine of said first adapter
4   before said loopback cell is transmitted over said ATM
5   network by said first adapter port.

12. A system for transmitting a loopback cell within a
switching node of an ATM connection, said switching node
including a first adapter having associated ports and a
second adapter having associated ports, wherein said
loopback cell enters said switching node by a first
adapter port, said system comprising:

processing means within said switching node for
detecting a loopback condition when an ATM cell enters
said first adapter;

a routing header function for appending a routing
label to said ATM cell indicating that said ATM cell is a
loopback cell to be looped back on said ATM connection;
and

a switching engine for transferring said loopback
cell to said first adapter port utilizing said appended
routing label.

13. The system of claim 12, further comprising an ATM
label lookup table for identifying said ATM cell within
said first adapter.

14. The system of claim 12, further comprising
processing means for reading a loop condition bit from a
dedicated register.

15. The system of claim 12, wherein said routing label
is appended to said loopback cell only if a loop control
bit is set by a control point of said switching node
within said first adapter.

16.   The system of claim 15, further comprising
processing means for setting said loop control bit within
said first adapter.

17.   The system of claim 15, further comprising
processing means for adding a loopback flag to said
loopback cell if said loop control bit is set, wherein
said loopback flag serves as an indicator for a protocol
engine within said first adapter that said routing labels
have to be appended to said loopback cell.

18.   The system of claim 12, wherein said routing label
includes a switch routing label for identifying said
first adapter as the output adapter from which said
loopback cell will exit said switching node.

19.   The system of claim 12, wherein said routing label
includes a protocol engine correlator for pointing to a
connection control block within said first adapter.

20.   The system of claim 12, wherein the ATM header
virtual path/virtual circuit of said loopback cell is not
swapped by the protocol engine of said first adapter
before said loopback cell is transmitted over said ATM
network by said first adapter port.